


#1401 Cork Insulation Tape

Technical Data

SEALANTS

Features and Benefits

- Adhesion: Excellent to commercially clean rubber, metal, glass, plastic or painted surfaces. Bonds firmly to itself, needing no supplemental adhesives.
- Wt. Per Gallon: Approximately 6.5 lbs.
- Odor: Imparts no odor. Can be used without danger of contamination.
- Color: Black
- Toxicity: Non-toxic, non-injurious, non-irritating to skin.
- Composition: Select grades of ground virgin cork and synthetic elastomeric materials.
- K-Factor: 0.430
- Shrinkage: Will not shrink, dry out, or pull away from surface. Properly applied, a firm bond is effected.
- Solids Content: 100% - 7 days @ 590° F.



DESCRIPTION:

#1401 Cork Insulation Tape is composed of select grades of ground virgin cork and synthetic elastomeric materials and it will not harden, skin over, lose its flexibility, shrink, dry out, or pull away from the surface when applied properly. Its excellent adhesion to all types of surfaces and ease of application make it adaptable for almost every cold insulating and sound deadening application.

USES:

#1401 Cork Insulation Tape was especially developed for the refrigeration and air-conditioning industries as an insulating material for cold pipes in air-conditioning systems, freezers, commercial refrigeration and wherever the problem of condensation is encountered. It also provides an effective sound deadening barrier and has been used successfully as a gasketing material.

Properties

Test Method

Value

Composition		Select grades of ground virgin cork and synthetic elastomeric materials.
Color		Black
Wt. Per Gallon		Approximately 6.5 pounds
Packaging		Extruded - Flat pack or rolls
Percent Solids		100% - 7 days @ 250° F
K-Factor		0.430
Oxidation		Will not harden, skin over, or lose its flexibility.
Adhesion		Excellent to commercially clean rubber, metal, glass, plastic, or painted surfaces. Bonds firmly to itself, needing no supplemental adhesives.
Shrinkage		Will not shrink, dry out, or pull away from surface. Properly applied, a firm bond is effected.

5017 South 38th Street
St. Louis, MO. 63116

Phone: 314-752-4667
Fax: 314-752-4035
Email: Info@SealersInc.com

SEALERS, INC.